

**SIMPLE OPERATION**

After pressing the start key, the fully automatic program sequence is executed with the preselected parameters. The parameters can be changed and adjusted during the mounting process.

**ELECTRONIC CONTROL**

With its clear LCD operation panel you can easily control the hot mounting press. You can load and save eighteen different mounting processes.



The Opal 480 is a fully hydraulic, water cooled hot mounting press for mounting samples before polishing.

The process sequence is executed automatically. The fully automatic sliding closure allows quick and easy opening/closing of the mould assembly.

Mould assemblies can be exchanged quickly and without tools. Also rectangular moulds can be produced. The robust aluminium construction is powder coated.

With its solid construction and QATM hydraulic system, the operating noise of the machine is minimized.

**MOULD ASSEMBLIES**

Our comprehensive selection of mould assemblies from  $\varnothing$  50 - 70 mm resp. 30x60/40x60 mm (rectangular form) enables optimum mounting of your sample. Two mounts can be produced simultaneously with the use of a spacer.

**PRESSURE MODE**

Besides the standard operation, you can choose between different pressure methods:

- | pressure increases parallel with the pre-heating phase (ideal for hollow specimens, e.g. rings).
- | pressure increases after the preset temperature is reached to produce mounts as gap free as possible (ideal for complex geometries).

**COOLING**

Not only the cooling time, but also the resulting cooling curve can be adjusted infinitely according to the mounting requirements. Thereby, a considerably lower water consumption is achieved for longer cooling times.

**HEATING**

Our high-power heating system gives a very short warm-up time. For delicate samples the machine can adjust the heating curve infinitely.

## SLIDING CLOSURE

The new sliding closure is a unique innovation and allows quick and easy opening/closing of the mould assembly. By actuating the lever, the closure slides to the correct position. After initiating the cycle the mould closes and reopens automatically on completion.



### BASIC MODULE

#### OPAL 480

- | automatic hot mounting press
- | fully hydraulic operation with automatic water cooling (with water saving function)
- | completely new and simple automatic closure system
- | computer controlled with automatic cycle processing
- | four different pressure modes
- | rectangular moulds
- | easy change of mould assemblies
- | aluminum case, powder coated

Order No.: M0790000

### EQUIPMENT

#### POWER SUPPLY

Equipment 1

230 V/50 Hz (1Ph/N/PE)

Order No.: A0790000

### ACCESSORIES

#### COOLING UNIT

##### Recirculation unit

| extern



Cooling	0.81 kW
Motor	0.6 kW
Flow pressure	2.8 bar
Tank	6 ltr.
WxHxD	440 x 345 x 565mm
230 V/50 Hz (1Ph/N/PE)	

Order No.: Z0730007

##### System cooling unit

| integrated in drawer



Cooling	0.81 kW
Motor	0.6 kW
Flow pressure	2.8 bar
Tank	6 ltr.
230 V/50 Hz (1Ph/N/PE)	

Order No.: A5810171

**ACCESSORIES**
**INSETS**
**Mould assemblies**


I cylinder, upper and lower ram

- Ø 50 mm                      **Order No.: Z0790000**
- Ø 60 mm                      **Order No.: Z0790001**
- Ø 70 mm                      **Order No.: Z0790002**
- 30x60 mm                  **Order No.: Z0790003**
- 40x60 mm                  **Order No.: Z0790004**

**Spacer**


I for double mounts

- Ø 50 mm                      **Order No.: 00702118**
- Ø 60 mm                      **Order No.: 00702025**
- Ø 70 mm                      **Order No.: 00702026**

**CONNECTION SET OPAL 480**

- 2x pressure tube              R ½"; 2 m long
- Adapter                          for ¾"

**Order No.: Z0730003**

I connection set for two Opal presses

**Order No.: Z0730004**
**SPECIFICATIONS**

Mould	Ø 50-70mm
Mould (rectangular)	30 x 60 / 40 x 60 mm
Connected load	3.6 kVA
Power supply	230 V/50 Hz (1Ph/N/PE)
Heating	4 x 630 Watt
Temperature range	20-200 °C
Heating time	variable / 0-30 min
Cooling time	variable / 0-30 min
Max. pressure	up to 310 bar depending on mould
WxHxD	~ 390 x 450 x 500 mm
Weight	68 kg

