UP200Ht – A Powerful and Smart Lab Sonicator www.hielscher.com/up200ht

| Ultrasonic Device UP200Ht | With the second seco | With a crylic sound protection box |
|--|---|---------------------------------------|
| Technical Details | UP200Ht : 200 watts, 26kHz; for handheld and stand-mounted use; automatic frequency tuning, amplitude adjustable from 20 to 100%, pulse adjustable from 0 to 100%, with colored touch-screen & digital control, operation and control via LAN, automatic data recording, dry running protected, IP30 grade, titanium horn Ø 10mm, amplitude at horn 70µm, in portable case | |
| Application | Homogenization, Dispersing & Deagglomeration (e.g. nano particles), Emulsifying, Lysis & Cell Disintegration, Extraction, Degassing, Sonochemistry | |
| Advantages | Performance: With 200 watts power, the UP200Ht is much more powerful than an ultrasonic bath or tank. Flexibility: For handheld or stand-mounted use, with various accessories for optimal adaption to your process. Comfortable Operation: The light-weight device is ergonomically designed. The operation settings can be adjusted via the colored touch-screen. All functions are easily and intuitively reachable through one main menu. Quality: The UP200Ht device fullfills the highest quality standards. All devices are designed, engineered and manufactured in Germany. | |
| Items: □ Ultrasonic Processor UP200Ht ○ 115 volts ○ 230 volts □ Sonotrode S26d2 (tip diameter 2mm) | | |

- □ Sonotrode S26d7 (tip diameter 7mm)
- □ Sonotrode S26d14 (tip diameter 14mm)
- $\hfill\square$ Stand ST1-16
- $\hfill\square$ Sound Protection Box SPB-L, made from acryl glass



nielscher ultrasonics

Hielscher Ultrasonics GmbH www.hielscher.com; info@hielscher.com Tel.: +49 (0)3328/437-420