



Military Ground Vehicles

FieldLab 58M is a battery-powered, integrated oil analysis system that provides quick and comprehensive oil analysis in the field.

Military and commercial field service professionals managing fleets of high-value assets require portable, lightweight devices that provide rapid oil analysis results with quality similar to oil analysis labs. Funded by the United States Department of Defense (DoD) in 2009, then developed and commercialized by Spectro Scientific, the FieldLab 58 Expeditionary Fluid Analysis System (EFAS) was designed for Military use.

The FieldLab 58 provides the ability to perform CBM (condition based maintenance) and warn of impending component failures by monitoring fluid chemistry, viscosity, particle contamination, and elemental analysis of wear debris.

Key Features


- Rugged design with battery power for on-site field use
- No solvents or chemicals required
- Complete oil analysis lab with 4 technologies integrated into a small case
 - X-Ray Fluorescence (XRF) spectrometer for elemental analysis
 - Filter Particle Quantifier (FPQ) pore blockage particle counter
 - Infrared (IR) spectrometer
 - Kinematic viscometer (40°C)
- 4 tests generate up to 20 oil analysis parameters in less than 10 minutes
- Built-in controller for measurement, data, and asset with touch screen interface
- Uses only 12 ml of oil
- ASTM compliant

FieldLab 58M COMPLETE IN-SERVICE OIL ANALYSIS LAB IN THE FIELD

Easy to Use

- No solvents or reagents and small sample volumes required
- Intuitive Interface and simple workflow minimizes human error
- Built-In Video Instruction for inexperienced users

Comprehensive Report and Adaptive Rules Engine



- Easy to read oil analysis report with clear Observations, Diagnostics, and Recommended Actions.
- Factory alarm limit tables for common components
- User-customizable alarm limits and diagnostic sets for continuous improvement over time

Optional Interface with TruVu 360 Fluid Intelligence Software

- Summary dashboards for visibility into asset condition and fleet readiness
- Management dashboard for CBM oil-analysis program management views of cost savings and program key performance indicators (KPIs)

KEY PARAMETERS



MACHINE WEAR

> Up to 16 elements for particles: Si, Al, Cr, Ti, Fe, Ni, Pb, Cu, Sn, Mo, Ag, Zn, V, Mg, W, Co



CONTAMINATION

> Particle count, ISO codes



> Water, glycol, soot



CHEMISTRY & VISCOSITY

> Oxidation, nitration, sulfation, TAN, TBN

> Viscosity @40°C, calculated viscosity @100°C




PRINCIPLES OF OPERATION

Particle count and elemental analysis – ASTM D8127


Particle counts are generated using our patented FPQ pore blockage particle counter (ISO 21018-3). It captures the particles of interest for severe wear detection onto a unique filtergram. This debris may now be measured on the companion XRF spectrometer for immediate results in ppm for up to 16 elements.

Wear and contamination particles larger than 4 microns deposit on the filtergram, and are tested using an X-Ray Fluorescence (XRF) spectrometer. The concentration (in ppm) for up to sixteen different elements is reported.


The filtergram coupon can be stored for future analysis, such as microscopic wear debris analysis of particle colors and shapes.



Oil Insertion




Particles





Filtergram

Fluid chemistry and contamination – ASTM D7889




The IR spectrometer measures the chemistry of the lubricant and contamination in one minute using only one drop of oil; no chemicals or solvents are required. It combines ease of use, ruggedness and laboratory precision in a small package, which is ideal for field use.

The oil condition parameters measured by FluidScan include oxidation, nitration, sulfation, anti-wear additive, Total Base Number (TBN), glycol, soot, and water for engine oil; and oxidation, Total Acid Number (TAN), and water for rotating machine lubricants such as gear oil, transmission oil and hydraulic oil.




IR Spectrum

Viscosity – ASTM D8092



Viscosity is measured using a temperature-controlled kinematic viscometer with a patented split-cell design.

A funnel, with a 100 micron gap, is formed in the center of the cell. Optical sensors in the cell detect the flow of oil under the influence of gravity. The time it takes the oil to flow through the cell is proportional to the viscosity of the oil. When open, the cells can be cleaned using a non-abrasive wipe. No solvents are required.



$$\text{Kinematic Viscosity (40°C)} = A * (t_1 - t_0) + B$$

*A and B are calibration coefficients



FieldLab 58M Product Information

| PRODUCT INFORMATION | |
|---|--|
| Part Numbers | FieldLab 58M (Ground) 800-00155 |
| Applications | Mineral and synthetic lubricants including gear, engines, transmissions, hydraulics, turbine as well as military, marine and mining applications |
| ELEMENTAL MODULE | |
| Detector | 25 mm ² SDD detector; Peltier cooled |
| Resolution | 122 eV FWHM resolution at 5.9 keV |
| Excitation Source | X-ray tube with Rhodium target; max voltage 50 kV |
| OPERATIONAL SPECIFICATIONS | |
| Sample Volume Required (all tests) | 12 ml to run all 4 tests |
| Sample Time Required | Less than 10 minutes through all 4 tests |
| Ambient Operating Temperature | 0° to 40°C |
| Operational Humidity | RH< 80% non-condensing |
| Ambient Altitude | Up to 5,000 meters (16,404 feet) |
| USER INTERFACE SPECIFICATIONS | |
| Display | Color touchscreen display |
| Data Storage | Internal flash memory, Optional USB thumb drive |
| Data Transfer | Ethernet, serial, optional USB |
| Data Entry | Desktop software via touchscreen or optional USB keyboard |
| POWER REQUIREMENTS | |
| Battery Power Source | Lithium-ion battery pack |
| Charge Power | 110/240 VAC, 50/60 Hz, 12 Watts |
| Typical Runtime | >3 hours on battery |
| Recharge Time | <3 hours |
| MECHANICAL SPECIFICATIONS | |
| Dimensions | Instrument: 19.2 x 15.2 x 9" Instrument in transit case 27.2 x 27.5 x 16.3" |
| Weight | 19 kg (42 lbs); 35 kg (77 lbs) in transit case |
| COMPLIANCE | |
| CENELEC EN 60610-1:2010 EN 61010-2-030 CENELEC EN 61326-2-1 MIL-STD 461 EMI MIL-PRF 28800F Class II Drop Test | |

| OUTPUTS | |
|-------------------------------------|---|
| Elemental Concentration (ppm) | Silicon (Si); Aluminum (Al); Chromium (Cr); Titanium (Ti); Iron (Fe); Nickel (Ni); Lead (Pb); Copper (Cu); Tin (Sn); Molybdenum (Mo); Silver (Ag); Zinc (Zn); Vanadium (V) Optional: Tungsten (W), Magnesium (Mg), Cobalt (Co) |
| Fluid Chemistry | TAN & TBN (mg KOH/g); Oxidation, Nitration, Sulfation (Abs/.1mm); Water (parts per million); Glycol (% by weight); Soot (% by weight); Incorrect fluid (% by weight); Antioxidant Depletion (% remaining); Antiwear Depletion (% by weight) |
| Viscosity | Kinematic viscosity @ 40°C Calculated viscosity @ 100°C |
| Particle Count | Particle count #/ml (> 4 µm) ISO Codes 4/6/14 ISO codes >6 and >14 are extrapolated |
| Methodology | ASTM D7889 (Chemistry) ASTM D8092 (Viscosity) ASTM D8127 (Particles and Elements) |
| Calibration | Factory, verification standards: NIST traceable verification standards provided |
| CONSUMABLES – FieldLab 58M (Ground) | |
| 800-00229 | FieldLab 58M Consumables Kit (without Verification Fluid), 100 pk |
| 600-00055 | FieldLab 58M Consumables Kit (without Verification Fluid), 500 pk |
| 600-00174 | FieldLab 58M/MA Standardization Kit |
| 600-00173 | FieldLab 58M/MA Verification Fluid |



For more info visit: www.spectrosci.com/fieldlab



Spectro Scientific | One Executive Drive, Suite 101, Chelmsford, MA 01824-2563 | 978-431-1120 | www.spectrosci.com | sales.spectrosci@ametec.com | An ISO 9001:2015 company

Copyright © 2022 Spectro Inc. All rights reserved. While every effort is made to assure the information in this document is accurate, Spectro does not accept liability for any errors or mistakes that may arise. Specifications are subject to change without notice.
FieldLab58M_DoDGround_BR_2022-10-06